



THE PROFESSIONALS CHOICE

SECURA III

STATIONARY TERMINAL



- Washing preparation supplied directly from the main warehouse
- Foam washing, disinfecting and rinsing in one appliance
 - Operator panel control
- Concentration selection by the supervisor (valve can be sealed)
 - Automatic flushing of the terminal
 - Intuitive operation
 - Safety

SECURA III STATIONARY TERMINAL

The Secura III Stationary Terminal is designed to supply via a pipeline concentrated washing preparations from the main warehouse. You can select the following functions: rinsing with water, active foam washing and disinfection. Functions are selected on the operator panel by pressing the appropriate button. Modern design compact housing made entirely of acid resistant stainless steel and easy operation and maintenance ensure long service life. Washing and disinfecting preparation is supplied in a form of a concentrate to the terminal via pipeline. The concentrate is pumped after selecting an appropriate function on the operator panel. Pumping switchboard controls the supply of the washing and disinfecting preparation. The appropriate dose of the preparation is dispensed by so called injector fitted with a special dispensing valve. Water under pressure of 16 to 25 bars is fed to a satellite unit from the KS-type pumping station, and compressed air is supplied from the customer's system. A special design of the internal fixtures causes the washing preparation intake system to flush each time the function on the panel is changed, which ensures the proper operation of the injector. The system controlling the modification of the operation mode prevents the operator error, i.e. mixing two different washing preparations.

Available accessories of the Secura III terminal:

- 220 mm foam lance
- 220 mm water lance
- 25m hose with lance connection
- Hanger for hose and lances
- Automatic hose reel



UNIT SPECIFICATION:

WATER DISCHARGE DURING RINSING	25 - 40 litres/min.
WATER DISCHARGE DURING FOAMING	8 - 10 litres/min.
MAXIMUM WATER TEMPERATURE	60°C
WATER PRESSURE	18 - 25 bars
AIR FLOW	200 litres /min
MAXIMUM AIR PRESSURE	8 bars
NOMINAL AIR PRESSURE	5 bars
CHEM. AGENT CONCENTRATION ADJUSTMENT RANGE	0 – 8%
DIMENSIONS	500 x 450 x 170 mm
WEIGHT	19,50 kg

KUCHNIE ŚWIATA S.A. 01-708 Warszawa, ul. Słodowiec 10/10
05-152 Czosnów, Łomna, ul. Gdańska 34 tel. +48(22)785-95-60, tel./fax +48(22)785-95-61
chemia@sanechem.com.pl, techniczny@sanechem.com.pl

Sales Office:
www.sanechem.com.pl